

# **CLEAR FRENCH CANDLE C22**

2W | 180 Lm | 2700K

Decorative, ultra dimmable LED filament light bulb with flicker-free technology and 30,000 hours lifetime. This lamp uses 2 watts of power to produce 180 lumens at a CRI of 90.

Item number: ZIK075/2W27E10C / ZIK075/2W27E14C



#### LAMP

Style	C22 French Candle
Socket	E10, E14
Filaments	2 x 38mm
Dimmable	Yes. Leading & trailing edge for
	E14, trailing edge only for E10.
LED Wattage	2w
Equivalent	20w
Lumen	180 lm
CCT	2700K
CRI	90
Glass finish	Clear
Warranty	3 years

### PERFORMANCE

Lifetime	30,000 hours
Cycles on/off	100,000
Starting time	<0.2 sec
Voltage	220v-240v
Hz	50/60 Hz
In-rush protection	3000V
Power factor	>0.9
Operating temperature	-30°c to +40°c
Energy Efficiency	90 lm/W
Energy Class	G( G -> A scale)
Energy Class	<b>G</b> ( G -> A scale)
Beam Angle	320°

### DIMENSIONS

Lamp Weight Inner / Outer carton q'ty 10 g 50 / 100

PAGE 1





NB! This light is for indoor use only and is not suitable for use in sealed fixtures, wet environments or for integral primary optics.



www.zico.lighting | +44 (0)20 7223 3087 | admin@zico.lighting ZICO LIGHTING 3rd Floor, 207 Regent Street, London W1B 3HH United Kingdom



## EAN13 CODES

**ZIK075/2W27E10C** 5060537721828 **ZIK075/2W27E14C** 5060537721408 Our lamps as well as the technologies behind them are subject to continuous improvements. All specification is subject to change without notice. Please refer to our website for the most up to date information.

Brand	Lamps tested	Dimmers Tested	Overall compatibility	Comments
<b>※LUTRON</b> 。	GLS A60 6W GOLFBALL G45 4W	<ul> <li>GP Panel</li> <li>NGRX Interface</li> <li>Homeworks QS Inline Dimmer</li> <li>myRoom DIN-rail Power Module (Phase Adaptive)</li> <li>RA2 Select In-Line Dimmer</li> </ul>	Excellent	See Test Report
LIGHTING	GLS A60 6W CANDLE C35 4W G9 3W	• Full Range	Excellent	Excellent on both leading and trailing edge
Powering Business Worldwide	CANDLE C35 4W PIGMY ST26 1W GLS A60 6W G9 3W	• Full Range	Very good	All lamps performed well without any issues. There were no current spikes, so, all are compatible with all of our dimmers
VARILIGHT®	CANDLE C35 4W PIGMY ST26 1W GLS A60 6W G9 3W	<ul> <li>V-PRO MJP120</li> <li>V-PRO MJP300</li> <li>V-PRO IR</li> <li>V-PRO MULTI-POINT</li> <li>V-COM 100</li> <li>V-COM 180</li> </ul>	Excellent	Excellent compatibility rating when driven in the recommended quantities. All lamps dimmed in a smooth, progressive fashion without flickering, over an extensive brightness range. The lamps extinguish fully when in the "off state" of our remote capable dimmers
rako	GLS A60 6W GOLFBALL G45 4W	• Full Range	Very Good / Excellent	This lamp performed very well with all dimmers with very few areas of criticism. No static flicker was observed at any output level although a slight shimmer while fading was observed with all dimmers except the WMT. While the profile was generally smooth and continuous there was a slight step around the minimum output level. Smoothness of Dimming Minimum brightness from off: <1% Minimum brightness from max: <1% Audible Noise: No audible
	GLS A60 6W	Full Range		noise when tested with any recommended dimmer. Very good
G Intecho	GOLFBALL G45 4W	- TUI Kunge		very good
Hospitality Solutions	GLS A60 6W GLS A60 10W GOLFBALL G45 4W GU10 6W	• Full Range	Very good	All the bulbs tested dim very well

PAGE 2